

**TO HELP DETERMINE WHICH ADAPTER YOU NEED BY
SUGINO DRILL MODEL NUMBER, USE THESE CHARTS.**

Conversion for Slimline Kinecheks

Sugino Drill Model #	Mounting Diameter	Deschner Adapter
ES2-U	0.94 "	None Req'd
ES3C	0.94 "	None Req'd
ES3P	0.94 "	None Req'd
ES4P	1.22 "	A15003
ES5	1.22 "	A15003
ES6	1.5 "	A15004
GSA	0.94 "	None Req'd
GSB	0.94 "	None Req'd
GSC	1.22 "	A15003
SFB	0.94 "	None Req'd
SFC	0.94 "	None Req'd

Conversion for Super-K Kinecheks

Sugino Drill Model #	Mounting Diameter	Deschner Adapter
ES2-U	0.94 "	A15005
ES3C	0.94 "	A15005
ES3P	0.94 "	A15005
ES4P	1.22 "	A15006
ES5	1.22 "	A15006
ES6	1.5 "	A15007
GSA	0.94 "	A15005
GSB	0.94 "	A15005
GSC	1.22 "	A15006
SFB	0.94 "	A15005
SFC	0.94 "	A15005

The use of a regulator provides adjustable feed rates, increases cycle times, reduces burring and drill breakage, and prevents sudden forward surges at drill breakthrough.